

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
16 June 2005 (16.06.2005)

PCT

(10) International Publication Number
WO 2005/054360 A2

- (51) International Patent Classification⁷: C08L 23/04 (81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (21) International Application Number: PCT/NL2004/000839
- (22) International Filing Date: 2 December 2004 (02.12.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
03078811.1 5 December 2003 (05.12.2003) EP
60/526,994 5 December 2003 (05.12.2003) US
- (71) Applicant (*for all designated States except US*): STICHTING DUTCH POLYMER INSTITUTE [NL/NL]; John F. Kennedylaan 2, NL-5612 AB Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (*for US only*): NOORDERMEER, Jacobus, Wilhelmus, Maria [NL/NL]; Millenerweg 6, NL-6118 BV Nieuwstadt (NL). NASKAR, Kinsuk [IN/NL]; Calslaan 45-11, NL-7522 MJ Enschede (NL).
- (74) Agent: JACOBS, Monique, Sophie, Nicole; DSM Intellectual Property, P.O. Box 9, NL-6160 MA Geleen (NL).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: PROCESS FOR THE PREPARATION OF A THERMOPLASTIC ELASTOMERIC VULCANIZATE

(57) Abstract: The invention deals with a process for the preparation of a thermoplastic elastomeric vulcanizate, based on a polyolefin and a rubber. The rubber is vulcanized with an organic peroxide having at least one terminal carbon-carbon bond in the molecule. As a result, blooming effects are reduced and physical properties are improved.

WO 2005/054360 A2